

CH13MS Flameless Heater

The CH13MS industrial heater uses a magnetic heat generating technology. With variable temperature and CFM settings, the heater is perfect for crucial applications

Features

- 750,000 BTU equivalent
- 150 – 160 ° F temperature rise
- Up to 5000 CFM
- >95% efficiency
- Dual 12" ducting
- Provision available to equip with light tower
- 8.2" above WC static pressure
- Self-contained unit with no external power source required
- Clean, breathable air
- Compact, portable design



Applications

- Drill deck, pump station and water line heating
- Snubbing stack heating
- Heating wellheads and BOPs
- Equipment thawing and deicing

Oil and Gas



- Concrete curing
- Ground thaw
- Aggregate Heating
- Worker Comfort Heating
- Hoardings heating
- Temporary site heating

Construction



- Tank coating and curing
- Surface Preparation
- Moisture and humidity control
- Dehumidification
- Deicing
- Auxiliary heat

Coatings and Painting



CAHILL HEATING Rentals

USA: Houston, TX / Canonsburg, PA / Rock Springs, WY / Brighton, CO

Canada: Red Deer, AB / Ft. McMurray, AB / Grande Prairie, AB

Telephone: 888.356.1880 / Email: info@cahillservices.com / www.CahillHeatingRentals.com

Technical specifications

Performance

BTU rating	750,000 equivalent
CFM range	Up to 5000
Static Pressure	8.2' above WC

Engine Data

Engine Type	Doosan
Electronics	Murphy

Fuel Data

Fuel Capacity	98 gallons
Fuel Type	Diesel
Fuel Consumption	3.6 gph

Dimensions

Height	Length	Width	Dry Weight
7'7"	12'6"	6'7"	3750 lbs

With our 24x7 service response model, we strive to eliminate downtime and guarantee fastest service turnaround.

The Cahill CH13MS heaters are available for SALES and RENTAL

For inquiries, please call us at 1.888.356.1880 or email us at info@cahillservices.com