

CH12MS - Flameless Heater

CLEAN-BREATHABLE AIR



Features

- 500,000 BTU equivalent
- Thermostatically controlled
- 150 F temperature rise
- Up to 4200 CFM
- CSA Field Certified
- Features a 5400 Lumen Light Stand
- 110% secondary containment
- Clean breathable air
- Self-contained unit with no external power source required
- Single 16" duct output
- Positive air shutoff
- Compact Portable Design

Technology

Performance

- 100% flameless magnetic heat production
- 110% built in secondary containment
- GPS location and runtime data

Fuel Data

- As low as 2.6 GPH fuel consumption
- 120 Gallon capacity
- 2.6 - 3.2 GPH

Heater Comparison

- Replace comparable flameless units 1 to 1
- Replace up to 3 indirect heaters with 1 CH12MS

Applications

- Drill deck, pump station and water line heating
- Snubbing stack heating
- Heating wellheads and BOPs
- Equipment thawing and deicing

Oil and Gas



- Concrete curing
- Ground thaw
- Aggregate Heating
- Worker Comfort Heating
- Multi-story construction heating

Construction



- Tank coating and curing
- Surface Preparation
- Moisture and humidity control
- Dehumidification
- Deicing
- Auxiliary heat

Coatings and Painting

