

CH14MS - Flameless Heater

THERMOSTATICALLY CONTROLLED



Features

- 1 million BTU equivalent
- Thermostatically controlled
- Hot air delivery up to 250 feet
- 160 F temperature rise
- Up to 6400 CFM
- >95% Efficiency
- 110% secondary containment
- Clean breathable air
- Self-contained unit with no external power source required
- Single 16" or Two 12" duct outputs
- Positive air shutoff
- Rugged design for increased durability

Technology

Performance

- 100% flameless magnetic heat production
- 110% built in secondary containment
- GPS location and runtime data

Fuel Data

- As low as 2 GPH fuel consumption
- 155 Gallon capacity
- 2 - 5.4 GPH

Heater Comparison

- Replace comparable flameless units 2 to 1
- Replace up to 6 indirect heaters with 1 CH14MS

Applications


• Drill deck, pump station and water line heating
• Snubbing stack heating
• Heating wellheads and BOPs
• Equipment thawing and deicing

Oil and Gas



• Concrete curing
• Ground thaw
• Aggregate Heating
• Worker Comfort Heating
• Multi-story construction heating

Construction



• Tank coating and curing
• Surface Preparation
• Moisture and humidity control
• Dehumidification
• Deicing
• Auxiliary heat

Coatings and Painting

